

Casters / Heavy Industrial

# 125mm Polyurethane Tyred Cast Iron Centred Wheel 330kg Capacity Castor

Model Number: S5548SLB



## Key features

The 125mm Polyurethane Tyred Wheel Richmond Castor - S5548SLB is a part of the significant series of heavy industrial castors. The wheel runs on Ball Bearings and the wheels diameter is 125mm (5"). More information on the Polyurethane Tyred Cast Iron Centred wheel can be found here. This heavy duty castor has a load capacity of 330kg. This castor is also fitted with a swivel lock. This frame allows the castor to swivel 360°. The S5548SLB is fitted with a brake. For the model without a brake click here. Our Polyurethane wheels are designed for durability, movability, shock absorbion and long life. This castor is quite versatile however it is popular in environments where floor protection and noise reduction is important.

## Specifications

|                                |                                      |
|--------------------------------|--------------------------------------|
| Product Code                   | S5548SLB                             |
| Wheel Diameter (mm)            | 125                                  |
| Frame Type                     | Swivel with Swivel Lock & Brake      |
| Wheel Width (mm)               | 38                                   |
| Wheel Type                     | Polyurethane Tyred Cast Iron Centred |
| Wheel Code                     | PU549                                |
| Wheel Bearing Type             | Ball Bearing                         |
| Castor Height (mm)             | 165                                  |
| Swivel Radius (mm)             | 145                                  |
| Maximum Load Capacity (kg)     | 330                                  |
| Recommended Load Capacity (kg) | 250                                  |