

PUNCTURE PROOF WHEELS

Puncture proof wheels are filled with foam instead of air, eliminating the possibility of punctures and flat tyres. They are a tough and reliable choice for use on nursery trolleys, hand trucks, wheelbarrows and other rolling equipment. They are available with steel or plastic rims to suit different applications.

- Foam filled tyres eliminate flats
- Plastic or steel rims
- Four tread patterns



UP TO
200KG
CAPACITY

PF1275



PF8881



PF1275



PF1642



PF1628

|  Nom Wheel Diameter (mm) |  Tyre Width (mm) |  Boss Width (mm) |  Axle Diameter |  Bearing Type |  Tyre Size |  Tyre Tread Pattern |  Load Capacity (kg) |  Wheel Centre |  Wheel Code |
|---|---|---|---|--|---|--|--|--|--|
| 215 | 55 | 60 | 1/2", 5/8", 3/4" or 20mm | Ball | 2.50 - 4 | Lug | 100 | Steel | PF8881 |
| 255 | 83 | 60 | 1/2", 5/8", 3/4" or 20mm | Ball | 4.10/3.50-4 | Industrial | 100 | Steel | PF1084 |
| 310 | 81 | 62 | 1", 3/4", 25mm, 20mm | Flange Ball | 4.10/3.50-6 | Diamond | 180 | Steel | PF1273 |
| 310 | 103 | 62 | 1", 3/4", 25mm, 20mm | Flange Ball | 13/5.00-6 | Turf | 200 | Steel | PF1275 |
| 400 | 150 | 102 | 1", 3/4", 25mm, 20mm | Flange Ball | 16x6.50-8 | Turf | 200 | Plastic | PF1628* |
| 400 | 93 | 76 | 1", 3/4", 25mm, 20mm | Flange Ball | 4.00-8 | Industrial | 200 | Steel | PF1632* |
| 400 | 150 | 102 | 1" | Nylon Bush | 16x6.50-8 | Turf | 200 | Plastic | PF1629 |
| 400 | 93 | 76 | 1" | Nylon Bush | 4.00-8 | Industrial | 200 | Steel | PF1641 |
| 400 | 100 | 75 | 1" | Ball | 400x8 | Knobby | 200 | Steel | PF1642 |
| 400 | 150 | 75 | 1" | Ball | 16x6.50-8 | Turf | 200 | Steel | PF1659 |
| 400 | 150 | 75 | 1" | Ball | 16x6.50-8 | Turf | 200 | Steel | PF1659 |

Tread Types



**NO
MORE
FLATS**

