

REBOUND RUBBER WHEELS

These wheels are non-marking, quiet, shock absorbing and have a low rolling resistance. They are ideal for moving lightly loaded equipment over uneven ground.

Rebound rubber wheels roll over small obstructions easily, and are commonly seen on waste bins, laundry trolleys, electrical equipment and other 'handle with care' goods. Stainless steel bearing models are also available.

- High shock absorbing qualities
- Non-marking
- Corrosion resistant models available



RR4473

 Wheel Diameter (mm)	 Tyre Width (mm)	 Boss Width (mm)	 Axle Diameter	 Bearing Type	 Load Capacity (kg)	 Wheel Code
75	30	41	8mm or 3/8"	Ball	80	RR3348
75	32	41	8mm or 3/8"	SS Ball	80	RR3367
75	30	39	1/2"	Plain	100	RR3370
100	30	41	8mm or 3/8"	Ball	100	RR4473
100	32	41	8mm or 3/8"	SS Ball	100	RR4367
100	30	39	1/2"	Plain	100	RR4470
100	35	46	8mm, 3/8", 12mm	Ball	150	RR4077
100	50	65	1/2" or 20mm	Ball	200	RR4078
125	30	42	8mm or 3/8"	Ball	100	RR5573
125	32	42	8mm or 3/8"	SS Ball	100	RR5637
125	30	39	1/2"	Plain	100	RR5570
125	35	46	8mm, 3/8" or 12mm	Ball	150	RR5077
125	50	65	1/2" or 20mm	Ball	250	RR5078
150	45	65	1/2" or 20mm	Ball	300	RR6677
200	45	65	1/2" or 20mm	Ball	300	RR8871



RR3367



RR5078



RR8871