

Casters / Heavy Industrial

125mm Polyurethane Tyred Nylon Centred Wheel 250kg Capacity Castor

Model Number: S5542SLB



Key features

The 125mm Polyurethane Tyred Wheel Richmond Castor - S5542SLB is in our large series of industrial castors. The wheel features Roller Bearings and the diameter of the wheel is 125mm (5"). Further information on the Polyurethane Tyred Nylon wheel can be found [here](#). This heavy duty castor has a load capacity of 250kg. This model is also fitted with a swivel lock. This castor features a swivel frame which allows the castor to swivel or rotate 360°. The S5542SLB is fitted with a brake. For the model without a brake [click here](#). Our Polyurethane wheels are designed for durability, movability, shock absorbbsion and long life. This castor is quite versatile however it is popular in environments where floor protection and noise reduction is important.

Specifications

Product Code	S5542SLB
Wheel Diameter (mm)	125
Frame Type	Swivel with Swivel Lock & Brake
Wheel Width (mm)	35
Wheel Type	Polyurethane Tyred Nylon Centred
Wheel Code	PU5508
Wheel Bearing Type	Roller Bearing
Castor Height (mm)	165
Swivel Radius (mm)	145
Maximum Load Capacity (kg)	250
Recommended Load Capacity (kg)	200